

# SUPPLIES & ACCESSORIES

## ELANCE



# Elace Vital Signs Monitor

# Elace Vital Signs Monitor

The élance family of integrated monitors offers you high-performance monitoring of essential parameters including ECG (3- and 5-lead), respiration, noninvasive blood pressure, peripheral O2 saturation and two temperatures. The “i” models add two channels of invasive blood pressure, and the “c” models add Microstream end tidal CO2.

Most TruLink supplies work with the Elance monitor:

- TruLink NIBP cuffs and hoses are compatible
- SpO2 sensors are compatible with same brand cable below
- TruLink ECG cables and leadwire systems are compatible



Elace Vital Signs Monitor 93300

Order Code	Description	Qty
<b>Supplies unique to the Elance monitor</b>		

### ECG Lead Wires & Cables (can also use standard TruLink ECG cables and leadwire systems)



<b>ECG Integrated Cables and Lead Wires</b>			
700-0008-22	5-lead Wire Set, Snap, Shielded, AAMI Color Coding, with Integrated Cable, Shielded	61cm/10in 305 cm/10 ft	1 Each
700-0008-23	5-lead Wire Set, Snap, Shielded, IEC Color Coding, with Integrated Cable, Shielded	61cm/10in 305 cm/10 ft	1 Each
700-0008-24	3-lead Wire Set, Snap, Shielded, AAMI Color Coding, with Integrated Cable, Shielded	61cm/10in 305 cm/10 ft	1 Each

### Spacelabs TruLink SpO2 Technology (use cable below with TruLink branded sensors only)



<b>SpO2 Cable</b>			
700-0287-00	SpO2 adapter cable	305 cm/10 ft	1 Each

### LNCS Masimo SET SpO2 Technology (use cable below with Masimo LNCS sensors only)



<b>LNCS Adapter Cable</b>			
690-0256-00	SpO2 Adapter Cable, Masimo, LNCS	305 cm/10 ft	1 Each

### Nellcor OxiMax SpO2 Technology (use cable below with Nellcor OxiMax sensors only)



<b>Cable</b>			
700-0290-00	SpO2 Adapter Cable, Nellcor OxiMax	305cm/10ft	1 Each

### Temperature



<b>Temperature Probe</b>			
690-0261-01	Skin/Surface Temp probe, reusable, YSI-400	305cm/10ft	1 Each

### Invasive Blood Pressure (See IBP section for compatible sensors and transducers)



<b>Interface Cable</b>			
690-0021-00	Compatible with Datex Ohmeda TC-VTK or Becton Dickinson model 684085 pressure transducers. See IBP section for other compatible supplies.	366 cm/12 ft	1 Each

### Recording & Printing



<b>Paper</b>			
307568-001	TruLink Thermal Paper, Z-fold Pads, 2- or 4-channel printing, blank paper, 300 sheets/pad	45.7 m/150 ft	10 Pads/Box

Indicates discontinued part, available while supplies last